

*Provides your Family
Safe Water for Better health... Better life*

**SPECIALLY DESIGNED FOR HARD WATER
(BORE WELL WATER; CITY COUNCIL WATER)**

Automatic Water Softener Small Features:-

- ◆ Fully Automatic microprocessor—controlled operation
- ◆ Self operation without assistance of technician at time of Regeneration.
- ◆ LCD Display, water flow, OBR and current status.
- ◆ Maintenance free. Durable & Volume base automatic multiport valve.
- ◆ Regenerates immediately when output volume drops zero thus providing each drop of soft water.
- ◆ No need to be present at the time of regeneration.
- ◆ LED display with 72 hours battery back up.
- ◆ Valve displays the remaining output of soft water before relegation for customer convenience.
- ◆ Compact Design & Seek Nominal Space.
- ◆ Seek & Stylish yet long durable cabinet.
- ◆ High-intensity FRP resin tank.
- ◆ Brine valve assembly with a float valve.
- ◆ Ideal for Bathroom, Washing machine, Dish washer & Gas geysers.



THE TECHNICAL SPECIFICATIONS:-

Product	AMRUT Automatic water softener small
Mode Of Operation	Automatic/ Manual
Max Purification Capacity	500 ltr/hr
Working Temp.	5°C ~ 50°C
Working Pressure	0.15 - 0.6 Mpa
OBR (Basis on 400ppm)	800 Liter
Resin Quantity	8 Liter
Salt Required for Regeneration	1.2 Kg
Brine Tank	Inbuilt
Inlet/outlet size	3/4"
Dimension in mm	L 200 x W 200 x H 1050



AMRUT FILTRATION AHMEDABAD 380004 INDIA EMAIL:INFO@AMRUTFILTRATION.COM

*Provides your Family
Safe Water for Better health... Better life*

**SPECIALLY DESIGNED FOR HARD WATER
(BORE WELL WATER; CITY COUNCIL WATER)**

Automatic Water Softener Small Features:-

- ◆ Fully Automatic microprocessor—controlled operation
- ◆ Self operation without assistance of technician at time of Regeneration.
- ◆ LCD Display at front cover for direct visibility of the operation.
- ◆ Maintenance free. Durable & Volume base automatic multiport valve.
- ◆ Regenerates immediately when output volume drops zero thus providing each drop of soft water.
- ◆ No need to be present at the time of regeneration.
- ◆ LCD display with 72 hours battery back up.
- ◆ Valve displays the remaining output of soft water before relegation for customer convenience.
- ◆ Compact Design & Seek Nominal Space.
- ◆ Seek & Stylish yet long durable cabinet.
- ◆ High-intensity FRP resin tank.
- ◆ Brine valve assembly with a float valve.
- ◆ Raw water available at the time of regeneration.
- ◆ Ideal for Bathroom, Washing machine, Dish washer & Gas geysers.



THE TECHNICAL SPECIFICATIONS:-

Product	AMRUT Automatic water softener Medium
Mode Of Operation	Automatic
Max Purification Capacity	1000 ltr/hr
Working Temp.	5°C ~ 50°C
Working Pressure	0.15 - 0.6 Mpa
OBR (Basis on 400ppm)	1900 Liter
Resin Quantity	12.5 Liter
Salt Required for Regeneration	2.8 Kg
Brine Tank	Inbuilt
Inlet/outlet size	3/4"
Dimension in mm	L 525 x W 325 x H 615



AMRUT FILTRATION AHMEDABAD 380004 INDIA EMAIL: INFO@AMRUTFILTRATION.COM

AUTOMATIC WATER SOFTNER BIG



Domestic | Commercial | Industrial

*Provides your Family
Safe Water for Better health... Better life*

**SPECIALLY DESIGNED FOR HARD WATER
(BORE WELL WATER; CITY COUNCIL WATER)**

Automatic Water Softener Small Features:-

- ◆ Fully Automatic microprocessor—controlled operation
- ◆ Self operation without assistance of technician at time of Regeneration.
- ◆ LCD Display, at front cover for direct visibility of the operation
- ◆ LCD Display, water flow, OBR and current status.
- ◆ Maintenance free. Durable & Volume base automatic multiport valve.
- ◆ Regenerates immediately when output volume drops zero thus providing each drop of soft water.
- ◆ No need to be present at the time of regeneration.
- ◆ LCD display with 72 hours battery back up.
- ◆ Valve displays the remaining output of soft water before relegation for customer convenience.
- ◆ Compact Design & Seek Nominal Space.
- ◆ Seek & Stylish yet long durable cabinet.
- ◆ High-intensity FRP resin tank.
- ◆ Brine valve assembly with a float valve.
- ◆ Ideal for individual Flat & Bungalow.



THECHNICAL SPECIFICATIONS:-

Product	AMRUT Automatic water softener Big
Mode Of Operation	Automatic
Max Purification Capacity	2000 ltr/hr
Working Temp.	5°C ~ 50°C
Working Pressure	0.15 - 0.6 Mpa
OBR (Basis on 400ppm)	4300 Liter
Resin Quantity	28 Liter
Salt Required for Regeneration	6.5 Kg
Brine Tank	Inbuilt
Inlet/outlet size	1"
Dimension in mm	L 525 x W 326 x H 1070



AMRUT FILTRATION AHMEDABAD 380004 INDIA EMAIL:INFO@AMRUTFILTRATION.COM

Safe Water for Better health... Better life

www.amrutfiltration.com